






# STEALTH ANCHOR SPECIFICATIONS

Product Code	E = EYE VERSION	Dimensions L x W x H (mm)	Materials	Typical Load Range	Minimum Driven Depth
S02E		70 x 24 x 20	Aluminium Alloy; Hard Anodised	0 - 2.5 kN	0.4 - 0.6m
S04E		121 x 41 x 34	Aluminium Alloy; Hard Anodised	1 - 10 kN	0.6 - 0.75m
S06E		171 x 58 x 50	Aluminium Alloy; Hard Anodised; Aluminium Bronze	5 - 25 kN	0.8 - 1.2m
S08E		263 x 90 x 76	Aluminium Alloy; Hard Anodised; Cast SG Iron; Aluminium Bronze	10 - 40 kN	1.1 - 1.5m
Product Code	T = T-LOC VERSION	Dimensions L x W x H (mm)	Materials	Typical Load Range	Driven Depth
S10T		375 x 115 x 101	Cast SG Iron; Aluminium Bronze	20 - 100 kN	2 - 3m

The quality and consistency of the soil/earth affect the typical load range of an earth anchor.

In a cohesive soil the full driven depth vertically/horizontally from ground level or beyond a failure plane may be required to achieve the lowest typical load.

In a non-cohesive/granular soil the shortest driven depth vertically/horizontally from ground level or beyond a failure plane may achieve the highest typical load.